

**Insulated Exhaust Pipe Wall/Roof Thimbles - Zero Clearance**  
**WT = Wall Thimble • RT = Roof Thimble • (WT or RT to precede Item#)**

NUMBER	ITEM #	A (Pipe)	B	C	D
1.0"	470100	1.375 ID	5.375	13	10.25
1.25"	470125	1.75 ID	5.75	13	10.25
1.5"	470150	2.0 ID	6.0	13	10.25
2.0"	470200	2.5 ID	6.5	14	11.5
2.5"	470250	3.0 ID	7.0	14	11.5
3.0"	470300	3.625 ID	7.625	15	12.0
3.5"	470350	4.125 ID	8.125	15	12.0
4.0"	470400	4.625 ID	8.625	20	14.25
5.0"	470500	5.625 ID	9.625	20	14.25
6.0"	470600	6.75 ID	10.75	22	16.25
8.0"	470800	8.875 ID	12.875	24	17.25
10.0"	471000	10.875 ID	14.875	28	20.5
12.0"	471200	12.875 ID	16.875	30	23.5
14.0"	471400	14.187 ID	18.187	30	23.5
16.0"	471600	16.187 ID	20.187	32	26.5
18.0"	471800	18.187 ID	22.187	32	26.5
20.0"	472000	20.187 ID	24.187	34	28.5
22.0"	472200	22.187 ID	26.187	36	30.5
24.0"	472400	24.187 ID	28.187	40	32.5
26.0"	472600	26.187 ID	30.187	42	34.5
28.0"	472800	28.187 ID	32.187	44	36.5
30.0"	473000	30.187 ID	34.187	46	38.5

\*For price information see Section 2 Page 11

**Recommended Application:**

- HAPCO Insulated exhaust roof and wall thimbles are recommended for use with exhaust pipes that must pass through a structure. The thimbles prevent exhaust pipe heat from being transmitted to the combustible material

**Features:**

- Insulated exhaust roof and wall thimbles are triple wall **ALL STAINLESS STEEL TYPE 304 CONSTRUCTION**
- Ventilation holes are located on each end to provide air cooling
- Screening is used on outlet end to prevent birds, rodents etc. from entering
- 24" is standard length, for longer requirements multiply list price X 4% for each additional inch
- Roofs with:  
 Pitch 1-12 to 3-12 add \$60.00  
 Pitch 4-12 and 5-12 add \$70.00  
 Pitch 6-12 and up add \$86.00

**Accessories:**

- Gaskets
- Fasteners

