

**HAPCO**  
**Spark Arresting Silencer (SASR)**  
**Residential Grade**

*U.S.F.S. qualified under Std. 5100-1 and Dept. of Defense spec. MIL A-27302A.*

SIZE MODEL	DWG #	CFM (MAX.)	DIA.	LENGTH	I.D. (INLET)	O.D. (OUTLET)	WT (Lbs.)
SASR 13	3210A-1	96	3.5	13	.5 - 1.25	1.25	6
SASR 24	3211A-1	167	4.5	15	1.25 - 1.75	1.75	7
SASR 36	3212A-1	205	6	22	1.75 - 2.5	2.50	12
SASR 48	3213A-1	485	7.5	26	2.5 - 3	3.00	17
SASR 59	3214A-1	705	8.25	30	3 - 3.5	4.00	25
SASR 69	3215A-1	1168	8.25	36	3.5 - 5	5.00	27

*Meets or exceeds U.S.F.S. Std. 5100-1 and Dept. of Defense spec. MIL A-237302A.*

SIZE MODEL	DWG #	A	B	C	D	E & F	WT (Lbs.)
SASR 13	3210A-1	.5 - 1.25	3.5	10	13	1.5	6
SASR 24	3211A-1	1.25 - 1.75	4.5	11	15	2	7
SASR 36	3212A-1	1.75 - 2.5	6	18	22	2	12
SASR 48	3213A-1	2.5 - 3	7.5	22	26	2	17
SASR 59	3214A-1	3 - 3.5	8.25	23	30	3.5	25
SASR 69	3215A-1	3.5 - 5	8.25	29	36	3.5	27
SASR 712	3216A-1	4 - 6	10	38	48	5	50
SASR 817	3217A-1	6 - 8.5	17	38	48	6	165
SASR 1024	3218A-1	8 - 12	24	54	68	7	325
SASR 1228	3219A-1	12 - 14	28	55	72	8.5	450

*\*For price information see Section 2 Page 2*

*\*Note Estimated weight only*

**Features:**

- Attenuation 8 - 19 dBA
- U.S.F.S. approved most sizes
- When ordering specify vertical or horizontal installation
- Optional side inlets and outlets, pipe threads, flanges and rain caps available, call for quote on sizes

**Accessories:**

- Rain cap
- Exhaust Elbows
- Mounting Bands
- Flange & Gasket Kits
- High Temp Blankets

